

Data Structure for Complexity Models

May 15, 2024

Import statement from "ri.newgen"

(Avoids conflicts between number types and types defined by the RI)

External Ppolynome

The domain **Ppolynome** is used to represent the complexities of the **statement** as function of parameters, variables and indices of loops with global coverage. A **Ppolynome** is a list of monomials, each monomial being constituted of a floating coefficient and a **Pvecteur** representing the product of variables with their exponents.

Complexity = eval:Ppolynome x varcount x rangecount x ifcount

In the course of the evaluation, a field **complexity** is associated with each **statement**. The sub-domain **eval** contains a polynome Approching the complexity of the statement. The sub-domains **varcount**, **rangecount** and **ifcount** give the information statistics concerning the manner in which the evaluation of the complexity took place, therefore also of the complexity itself. They count and in so doing classify the different types of variables/loops/tests encountered in the course of the complexity's evaluation.

Varcount = symbolic:int x guessed:int x bounded:int x unknown:int

- **symbolic** = the number of variables which we would like to see appear in symbolic form in the expression of the complexity ("parameters" Fortran, loop indices, formal parameters of a subroutine). This gives false results of this type of variable is modified in the course of execution.
- **guessed** = the number of variables the values of which we have guessed thanks to semantic analysis.
- **bounded** = the number of variables for which we have determined a maximum or minimum thanks to semantic analysis.
- **unknown** = the number of for which we have found no information, and which the user has not asked to be displayed in the complexity. These variables are all replaced by the pseudo-variable **UNKNOWN_VARIABLE**, which takes at the end of the evaluation a default value.

Rangecount = profiled:int x guessed:int x bounded:int x unknown:int

- **profiled** = the number of loops for which the limits have been measured by means of profiling.
- **guessed** = the number of loops for which the limits were at worst variable polynomes of type **symbolic** or **guessed**
- **bounded** = the number of loops for which the min./max limits were deterlined thanks to semantic analysis.
- **unknown** = the number of loops for which the number of loops could not be discovered. In consequence 0 after profiling pass. All these numbers are replaced by the pseudo-variable: `UNKNOWN_RANGE`, which will be given a default value at the end.

`Ifcount = profiled:int x computed:int x halfhalf:int`

- **profiled** = the number of tests for which the probability was measured by mens of profiling .
- **computed** = the number of tests for which the probability the probability was calculated. In particular in this case where the boolean expression depends only on the indices of those loops whose coverage global and whose **ranges** are of type **guessed**.
- **halfhalf** = the number of tests the probability of which was determined to be equal to a $\frac{1}{2}$ by defaut.